

## 10 - 500 µL PTFE Tipped Plunger

SPECIFICATIONS	
Accuracy and Reproducibility	± 1 % (dispensed volume)
Borosilicate Glass Barrel Outer Diameter (OD)	10 µL = 6.5 mm, 25 - 500 µL = 8 mm
Scale Length	10 µL = 54.1 mm, 25 - 500 µL = 60 mm
International Standards Traceability	

Syringe Volume	PTFE Tipped Plunger	Needle Length (mm)	Needle Gauge	Needle OD (mm)	Needle ID (mm)	Needle Tip	Syringe Code	Replace-ment Needle Part No.	Replace-ment Plunger Part No.	6 Pack Syringe Part No.	Syringe Part No.
<b>Fixed Needle</b>											
10 µL	✓	50	26	0.47	0.11	Bevel	10F-GT	-	031810	002202	002200
10 µL	✓	70	26	0.47	0.11	Bevel	10F-GT-7	-	031810	-	002208
25 µL	✓	50	25	0.50	0.20	Bevel	25F-GT	-	031815	-	003200
50 µL	✓	50	25	0.50	0.20	Bevel	50F-GT	-	031820	-	004200
100 µL	✓	50	25	0.50	0.20	Bevel	100F-GT	-	031825	-	005200
250 µL	✓	50	25	0.50	0.20	Bevel	250F-GT	-	031830	-	006200
500 µL	✓	50	25	0.50	0.20	Bevel	500F-GT	-	031835	-	007200
<b>Removable Needle</b>											
10 µL	✓	50	26	0.47	0.11	Bevel	10R-GT	037110	031811	002252	002250
25 µL	✓	50	25	0.50	0.20	Bevel	25R-GT	038110	031815	-	003250
50 µL	✓	50	25	0.50	0.20	Bevel	50R-GT	038110	031820	-	004250
100 µL	✓	50	25	0.50	0.20	Bevel	100R-GT	038110	031825	-	005250
250 µL	✓	50	25	0.50	0.20	Bevel	250R-GT	038110	031830	-	006250
500 µL	✓	50	25	0.50	0.20	Bevel	500R-GT	038110	031835	-	007250
<b>Guided Plunger</b>											
10 µL	✓	50	26	0.47	0.11	Bevel	10R-GP-GT	037110	031805	-	002455
<b>On-Column</b>											
10 µL	✓	75	-	0.17	0.11	On-Column	10R-GT-OC-CE	037675	031811	-	002500
<b>Fixed Luer Tip</b>											
50 µL	✓	-	-	-	-	-	50F-LT-GT	-	031820	-	004229
100 µL	✓	-	-	-	-	-	100F-LT-GT	-	031825	-	005229
250 µL	✓	-	-	-	-	-	250F-LT-GT	-	031830	-	006229
500 µL	✓	-	-	-	-	-	500F-LT-GT	-	031835	-	007229
<b>Fixed Luer Lock</b>											
50 µL	✓	-	-	-	-	-	50F-LL-GT	-	031820	-	004230
100 µL	✓	-	-	-	-	-	100F-LL-GT	-	031825	-	005230
250 µL	✓	-	-	-	-	-	250F-LL-GT	-	031830	-	006230
500 µL	✓	-	-	-	-	-	500F-LL-GT	-	031835	-	007230

Syringes and Accessories

