


NEW Rtx®-BAC Plus 1 and Rtx®-BAC Plus 2 Columns

Fast, Definitive Data for Blood Alcohol Testing

- Optimized column selectivities guarantee resolution of ethanol, internal standards, and frequently encountered interferences.
- Robust and reproducible column chemistry ensures longer column lifetime and accurate, consistent results.
- 2 minute analysis time increases lab productivity.

New Rtx®-BAC Plus 1 and Rtx®-BAC Plus 2 columns from Restek are designed to provide definitive results quickly, so you can maximize sample throughput. These columns baseline separate all critical compounds, including ethanol, methanol, acetone, *tert*-butanol (IS), acetaldehyde, isopropanol, and 1-propanol (IS), in less than 2 minutes (Figure 1). In fact, every Rtx®-BAC Plus 1 and Plus 2 column is quality tested with these important target compounds to ensure performance. These new columns are exceptionally robust, ensuring longer column lifetime and highly reproducible data. For fast, consistent results, try Rtx®-BAC Plus 1 and Rtx®-BAC Plus 2 columns for analysis of blood alcohol compounds.

Figure 1 NEW Rtx®-BAC Plus 1 and Rtx®-BAC Plus 2 columns baseline resolve all critical components in less than 2 minutes!



NEW Columns and Standards for Blood Alcohol Testing

Rtx®-BAC Plus 1/Rtx®-BAC Plus 2 Columns

- Optimized column selectivities guarantee resolution of ethanol, internal standards, and frequently encountered interferences.
- Robust and reproducible column chemistry ensures longer column lifetime and consistent results.

Rtx®-BAC Plus 1 Columns (fused silica)

ID	df	temp. limits	30-Meter
0.32mm	1.80µm	-20 to 240/260°C	18004
0.53mm	3.00µm	-20 to 240/260°C	18005

Rtx®-BAC Plus 2 Columns (fused silica)

ID	df	temp. limits	30-Meter
0.32mm	0.6µm	-20 to 240/260°C	18006
0.53mm	1.0µm	-20 to 240/260°C	18007



Visit www.restek.com/cft for the latest products and resources for clinical, toxicology, and forensic laboratories.

Blood Alcohol Resolution Control Standards

- Use to verify the retention time for each compound normally included in a blood alcohol test, and to verify that the compounds are resolved from and do not interfere with one another.
- Includes 1-propanol or *tert*-butanol internal standard.
- Intended for qualitative use only.

BAC Resolution Control Standard n-P (6 components)

acetaldehyde	methanol
acetone	1-propanol
ethanol (BAC)	2-propanol (isopropanol)
100mg/dL each in water, 1mL/ampul	

cat.# 36010 (ea.)

No data pack available.

BAC Resolution Control Standard t-B (6 components)

acetaldehyde	ethanol (BAC)
acetone	methanol
<i>tert</i> -butanol (TBA)	2-propanol (isopropanol)
100mg/dL each in water, 1mL/ampul	

cat.# 36011 (ea.)

No data pack available.

Blood Alcohol Standards (Calibration)

- NIST-traceable ethanol calibration standards.
- Calibration mixtures ranging from 0.010g/dL to 0.40g/dL in water.
- Datapack and Certificate of Analysis for each standard available on our website.

Compound	qty.	cat.#
0.010g/dL forensic ethanol solution	1 mL/ampul	5-pk.
0.015g/dL forensic ethanol solution	1 mL/ampul	5-pk.
0.02g/dL forensic ethanol solution	1 mL/ampul	5-pk.
0.025g/dL forensic ethanol solution	1 mL/ampul	5-pk.
0.04g/dL forensic ethanol solution	1 mL/ampul	5-pk.
0.05g/dL forensic ethanol solution	1 mL/ampul	5-pk.
0.08g/dL forensic ethanol solution	1 mL/ampul	5-pk.
0.1g/dL forensic ethanol solution	1 mL/ampul	5-pk.
0.15g/dL forensic ethanol solution	1 mL/ampul	5-pk.
0.16g/dL forensic ethanol solution	1 mL/ampul	5-pk.
0.2g/dL forensic ethanol solution	1 mL/ampul	5-pk.
0.3g/dL forensic ethanol solution	1 mL/ampul	5-pk.
0.4g/dL forensic ethanol solution	1 mL/ampul	5-pk.

PATENTS & TRADEMARKS

Restek patents and trademarks are the property of Restek Corporation. Other trademarks appearing in Restek literature or on its website are the property of their respective owners. The Restek registered trademarks used here are registered in the United States and may also be registered in other countries.



Restek U.S. • 110 Benner Circle • Bellefonte, PA 16823 • 814-353-1300 • 800-356-1688 • fax: 814-353-1309 • www.restek.com

Restek France • phone: +33 (0)1 60 78 32 10 • fax: +33 (0)1 60 78 70 90 • e-mail: restek@restekfrance.fr

Restek GmbH • phone: +49 (0)6172 2797 0 • fax: +49 (0)6172 2797 77 • e-mail: info@restekgmbh.de

Restek Ireland • phone: +44 (0)2890 814576 • fax: +44 (0)2890 814576 • e-mail: restekireland@aol.com

Restek Japan • phone: +81 (3)6459 0025 • fax: +81 (3)6459 0025 • e-mail: restekjapan@restek.com

Thames Restek U.K. LTD • phone: +44 (0)1494 563377 • fax: +44 (0)1494 564990 • e-mail: sales@thamesrestek.co.uk

Lit. Cat.# CFTS1483-UNV

© 2011 Restek Corporation. All rights reserved.
Printed in the U.S.A.

